


N 70, Integrated box hood, 60 cm, clear glass white printed
D64XAF8NOB



COOKING PASSION SINCE 1877



B



Our invisible integrated canopy box hood - perfectly integrated with extra storage for easy access items, such as spices and herbs.

- ✓ LED lighting: a clear illumination whilst cooking thanks to the energy-saving LED lights
- ✓ Hidden Design – integrate your hood seamlessly and blend it top to bottom with our flush-fitted design in your cupboard
- ✓ Extra Storage – the hood's T-shaped body makes more of your cabinet with extra space for many large and handy items
- ✓ High extraction rate: Ensures a clear view while cooking thanks to efficient motor technology as either a ducted or recirculating solution.

Features

Technical Data

Approval certificates : CE
 Length electrical supply cord (cm) : 150
 Required niche size for installation (HxWxD) : 356mm x 562.0mm x 310mm
 Height of product, without chimney (mm) : 60
 Minimum distance above an electric hob : 500
 Minimum distance above a gas hob : 500
 Net weight (kg) : 15,246
 Type of control : mechanical
 Number of speed settings : 3
 Maximum output air extraction (m³/h) : 610
 Number of lights : 2
 Noise level (dB(A) re 1 pW) : 70
 Diameter of air outlet (mm) : 150
 Grease filter material : Washable aluminium
 EAN code : 4242004243618
 Connection Rating (W) : 255
 Voltage (V) : 220-240
 Frequency (Hz) : 50; 60

Optional accessories

Z51IBNON0	Chimney extension 187-360mm
Z51IBUOX0	Standard recirculation kit
Z51IMA0X0	Standard odor filter (replacement)
Z51ITPOX0	Long Life odor filter (replacement)
Z54TR00X0	gleanAir active carbon filter
Z54TR60X3	CleanAir Recirculation Kit



*N 70, Integrated box hood, 60 cm, clear glass white
printed
D64XAF8NOB*

Features

Key performance features:

- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 max. 610 m³/h
- Noise max. Normal Level: 70 dB*

Features

- 3 power levels via rotary switch, retractable
- White with LED backlit glass panel
- 2 x LED 2.5W
- Colour Temperature: 3500 K
- Filter cover glass, metal grease filter
- 1 metal grease filter cassette
- For installation in a kitchen cabinet

Design

- Adjustable glass visor for additional vapour capture
- Filler strip for an individual depth adjustment in cupboard up to maximum 350 mm.
- Mechanical controls

Performance/technical information

- Suitable for ducted extraction and recirculation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Max. extraction rate: 610 m³/h
- Extraction rate according to EN 61591 max. 610 m³/h
- Noise max. Normal Level: 70 dB*
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 70 dB(A) re 1 pW (57 dB(A) re 20 µPa sound pressure)
-
- Light Intensity: 76 lux
- Colour Temperature: 3500 K
- Electrical cable length 1.5 m
- Diameter pipe Ø 150 mm (Ø 150 mm enclosed)
- Dimensions (HxWxD): 356 x 594 x 310 mm
- Built-in dimensions (HxWxD): 356 x 562 x 310-350 mm
- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Blower Efficiency Class: B*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: C*
- Average Energy Consumption: 61 kWh/year*

Optional accessories

- Recirculating kit

* In accordance with the EU-Regulation No 65/2014